

* PRODUCT INFORMATION *

HUSKEY™ 650 H.T. OIL

DESCRIPTION

HUSKEY 650 HT OIL is a blend of the finest quality pure synthetic base oil and additives available and is formulated with Molybdenum Disulfide (Moly). Superior performance capabilities are derived from special properties of the synthetic base oil coupled with extreme pressure and anti-wear additives. **HUSKEY 650 HT OIL OPERATING RANGE** - Base Oil -35EF to 500EF with dry film lubrication to 850EF.

USAGE

HUSKEY 650 HT OIL was designed for chain and bearing applications in lithograph ovens, heat treating, paint dryers, kilns, tenter frame chains and most other high temperature conditions.

ADVANTAGES

- **PLATING ACTION:** Fortified with sub-micron size moly particles, it impregnates the metal surface, improving filling in the metal imperfections.
- **FRICITION IS LOWERED:** By the unique quality of moly reducing contact area temperature, resulting in increased working life of both the oil and the metal surface.
- **CLEANSING ACTION:** The outstanding feature of this oil is its lack of carbon residue or tendency to form sludge or varnish deposits as higher temperatures are reached.

TYPICAL SPECIFICATIONS

Color	Moly Gray	Pour Point,EF	-35
Base Type	Synthetic	Viscosity Index, Min	85
Flash Point, EF	500	Conradson Carbon, %	.001
Viscosity SUS @ 100EF	454	Gravity, API	11.3
Viscosity SUS @ 210EF	58	Evaporation Loss, %	2
4-ball Wear Scar, mm		(6½ hrs. at 400EF)	
(40 Kg, 1 hr, @ 1200 rpm, 167EF)	0.5	Base Solid	Molybdenum Disulfide

NOTE: *HUSKEY* synthetic oils may not be compatible with some petroleum oils.

PACKAGE AVAILABILITY

1-gal Jug (4/case), 5-gal. Pail, 15-gal. Keg and 55-gal. Drum

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

1/04



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE