

# POLYIMIDE DISCS

## 500 °F (260 °C)

Part Number	Diameter			Quantity Per Roll
	Fraction (in)	Decimal (in)	Metric (mm)	
KP00125	1/8	0.125	3.18	2000
KP00187	3/16	0.187	4.75	2000
KP00250	1/4	0.250	6.35	2000
KP00312	5/16	0.312	7.92	2000
KP00375	3/8	0.375	9.53	2000
KP00437	7/16	0.437	11.10	2000
KP00500	1/2	0.500	12.70	2000
KP00562	9/16	0.562	14.27	2000
KP00625	5/8	0.625	15.88	2000
KP00687	11/16	0.687	17.45	1000
KP00750	3/4	0.750	19.05	1000
KP00812	13/16	0.812	20.62	1000
KP00875	7/8	0.875	22.23	500
KP00937	15/16	0.937	23.80	500
KP01000	1	1.000	25.40	500
KP01062	1-1/16	1.062	26.97	500
KP01125	1-1/8	1.125	28.58	500
KP01187	1-3/16	1.187	30.15	500
KP01250	1-1/4	1.250	31.75	500
KP01312	1-5/16	1.312	33.32	500
KP01375	1-3/8	1.375	34.93	500
KP01437	1-7/16	1.437	36.50	500
KP01500	1-1/2	1.500	38.10	500
KP01562	1-9/16	1.562	39.67	500
KP01625	1-5/8	1.625	41.28	250
KP01687	1-11/16	1.687	42.85	250
KP01750	1-3/4	1.750	44.45	250
KP01812	1-13/16	1.812	46.02	250
KP01875	1-7/8	1.875	47.63	250
KP01937	1-15/16	1.937	49.20	250
KP02000	2	2.000	50.80	100
KP02250	2-1/4	2.250	57.15	100
KP02500	2-1/2	2.500	63.50	100
KP02750	2-3/4	2.750	69.85	100
KP03000	3	3.000	76.20	100
KP03250	3-1/4	3.250	82.55	100
KP03500	3-1/2	3.500	88.90	100
KP03750	3-3/4	3.750	95.25	100
KP04000	4	4.000	101.60	100
KP04250	4-1/4	4.250	107.95	100
KP04500	4-1/2	4.500	114.30	100
KP04750	4-3/4	4.750	120.65	100
KP05000	5	5.000	127.00	100
KP05250	5-1/4	5.250	133.35	100
KP05500	5-1/2	5.500	139.70	100
KP05750	5-3/4	5.750	146.05	100
KP06000	6	6.000	152.40	100



- Recommended for high-temp powder coating and masking gold leaves of PCB during wave soldering
- Offers optimum performance in thermal insulation
- Offers flame resistant electrical insulation
- Other sizes available